

EBA 280/280 S

Small centrifuges

Practical: The rotor can be quickly changed to offer maximum adaptability



EBA 280 / 280 S



View into the centrifuging chamber
showing the rotor 1146
with blood collection tubes

THESE SMALL CENTRIFUGES OFFER MAXIMUM USER COMFORT

The EBA 280 and EBA 280S offer exceptional user comfort for small centrifuges and a choice between six rotors. Thanks to a newly-developed rapid changeover system it is possible to quickly switch from one rotor to another, without the need to use any tools and with just one hand. The rotor locks automatically in place and sits securely without the need for screws or tightening.

With the 1146 swing-out rotor the EBA 280 achieves an RCF of 3,112 with up to six 15-ml tubes. The higher-performance EBA 280S can achieve a maximum RCF of 5,071 with the same tubes. This corresponds to 6,000 RPM. With run-up and run-down times of 11 resp. 13 seconds, emergency samples can be processed within a few minutes.

Both models are suitable for use in medical diagnostics, environmental analysis and research labs, for example for the sedimentation of cells and yeasts or to clarify water and soil samples.



EBA 280
Small centrifuge

Cat. No. 1101



EBA 280S
Small centrifuge

Cat. No. 1102

EBA 280 / 280 S



COMPREHENSIVE RANGE OF ACCESSORIES

Both the EBA 280 and the EBA 280S can be used with three angle rotors and three swing-out rotors. The swing-out rotors have an integrated base on which they can stand. They can thus be loaded in comfort outside the centrifuge. All of the common blood collection tubes, urine tubes, screw-top tubes and glass tubes up to 50 ml can be used with adapters. Cells may also be washed in the 1133 decanting rotor.

SOPHISTICATED CONTROL SYSTEM

In addition to the innovative rotor changeover system, the EBA 280 and EBA 280S also feature versatile control systems. The systems are programmable, with 10 memory slots. The parameters time, RPM and RCF can easily be entered via arrow keys. A choice of nine resp. ten ramps is available for the run-up and run-down times.



AT A GLANCE



FIELDS OF APPLICATION

• Medical diagnostics

Centrifugation of blood and urine samples

• Environmental analyses

Clarification of water and soil samples

• Research

Sedimentation of cells, yeast cells, bacteria, etc.

EASE OF OPERATION

- Rapid and easy change of rotors through the rapid rotor change system
- Control system with 10 programmable memories
- Swing-out rotors with integrated stand
- Rapid and precise setting of centrifugation time, RPM and RCF via arrow keys
- Entry of run-up and run-down times in ramps of 1 (0) to 9

SAFETY

- Lid locking and holding
- Lid dropping protection
- Imbalance switch-off
- Emergency lid lock release

DESIGN

- Compact design, saving space
- Smooth plastic housing, easy to clean
- Centrifuging chamber of stainless steel
- Metal lid
- Backlit LCD display

MAX. RCF

- 4,146 (EBA 280)
- 5,071 (EBA 280S)

MAX. CAPACITY

- 6 x 50 ml

EBA 280 / 280S IN ACTION

Scan the QR code or follow this link:
<http://youtu.be/6GSCMYsszs4>



ACCESSORIES




























Swing-out rotor, 6-place



$\angle 90^\circ$
 $n = 4,700 \text{ min}^{-1} / 6,000 \text{ min}^{-1}$
 max. RCF 3,112/5,071

Cat. No. (without carriers) 1146

capacity in ml	0.5	4	5	6	15	1.1 – 1.4	2.6 – 3.4	2.7 – 3	4 – 5.5
Ø x L in mm	10.7 x 36	10 x 88	12 x 75	12 x 82	17 x 100	8 x 66	13 x 65	11 x 66	15 x 75
Cat. No.	Pediatric	-	0553 ¹⁾	0501 ¹⁾	0518 ¹⁾	blood collection/urine tubes			
carriers Cat. No. 1147-6 (6 pcs.)									
 rotor Cat. No. 1146									
Cat. No.	1063-6 (6 pcs.)	-	1053-6 (6 pcs.)	0767-6 (6 pcs.)	-	1053-6 (6 pcs.)			-
boring Ø x L in mm	11 x 35	17.5 x 80	13.5 x 59	17.5 x 80	17.5 x 80	13.5 x 59			17.5 x 80
tubes per rotor	6								
max. RCF ¹⁾ EBA 280	1,877	3,112	2,618	2,865	3,112	2,618			3,112
max. RCF ¹⁾ EBA 280 S	3,059	5,071	4,266	4,669	5,071	4,266			5,071
radius in mm	76	126	106	116	126	106			126
run-up in sec	9 (EBA 280) / 11 (EBA 280 S)								
run-down in sec, braked	11 (EBA 280) / 13 (EBA 280 S)								

capacity in ml	4.5–5	4.9	7.5–10	1.6–5	4–7	4–7	8.5–10	12
Ø x L in mm	11 x 92	13 x 90	15/16 x 92	13 x 75	16 x 75	13 x 100	16 x 100	17 x 102
Cat. No.	blood collection / urine tubes							
carriers Cat. No. 1147-6 (6 pcs.)								
 rotor Cat. No. 1146								
Cat. No.	-			1053-6 (6 pcs.)	0767-6 (6 pcs.)	-		
boring Ø x L in mm	17.5 x 80			13.5 x 59	17.5 x 80	17.5 x 80		
tubes per rotor	6							
max. RCF ¹⁾ EBA 280	3,112			2,618	2,865	3,112		
max. RCF ¹⁾ EBA 280 S	5,071			4,266	4,669	5,071		
radius in mm	126			106	116	126		
run-up in sec	9 (EBA 280) / 11 (EBA 280 S)							
run-down in sec, braked	11 (EBA 280) / 13 (EBA 280 S)							

¹⁾ Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers. The max. RCF for glass tubes annotated with footnote ¹⁾ is 4,000.

ACCESSORIES



Swing-out rotor, 8-place



$\angle 90^\circ$
 $n = 5,000 \text{ min}^{-1}$
 max. RCF 2,991
















Cat. No. (without carriers) 1148







Swing-out rotor, 12-place



$\angle 60^\circ$
 $n = 5,000 \text{ RPM}$
 max. RCF 2,963

Cat. No. (without carriers) 1142

capacity in ml	5	6	10	2.6–3.4	2.7–3	4–5.5	1.6–5	4–7
Ø x L in mm	12x75	12x82	17x70	13x65	11x66	15x75	13x75	16x75
Cat. No.	0553 ¹⁾	0501 ¹⁾	2079	blood collection / urine tubes				
 rotor Cat. No. 1148								
								
Cat. No.	1131-A		1132-A	1131-A		1132-A	1131-A	1132-A
boring Ø x L in mm	13x53		17.5x53	13x53		17.5x53	13x53	17.5x53
tubes per rotor	8							
max. RCF ¹⁾	2,991							
radius in mm	107							
run-up in sec	8							
run-down in sec, braked	10							

capacity in ml	5	2.6–3.4	2.7–3	1.6–5
Ø x L in mm	12x75	13x65	11x66	13x75
Cat. No.	0553¹⁾	blood collection / urine tubes		
 rotor Cat. No. 1142				
				
Cat. No.	1127-A			
boring Ø x L in mm	13.2x53			
tubes per rotor	12			
max. RCF ¹⁾	2.963			
radius in mm	106			
run-up in sec	10			
run-down in sec, braked	12			

ACCESSORIES



Angle rotor, 12-place, for decanting



✂35°
n = 5,000 min⁻¹
max. RCF 2,879

Cat. No. 1133

Angle rotor, 6-place



✂35°
n = 6,000 min⁻¹
max. RCF 4,025

Cat. No. 1137

capacity in ml	5	6	7
Ø x L in mm	12x75	12x82	12x100
Cat. No.	0553¹⁾	0501¹⁾	0578¹⁾


























rotor
Cat. No. 1133

Cat. No.	-
boring Ø x L in mm	12.5 x 66
tubes per rotor	12
max. RCF ¹⁾	2,879
radius in mm	103
run-up in sec	8
run-down in sec, braked	10

Rotor 1133

What makes the 1133 rotor special is its adapters with a decanting aid. The decanting aid firmly holds the tube and keeps it from falling out when the supernatant is decanted.

The 1133 rotor is often used in blood group serology.

capacity in ml	7	15	25	50	9–10	10	1.6–5	4–7	15	50	30	50
Ø x L in mm	12 x 100	17 x 100	24 x 100	34 x 100	16 x 92	15 x 102	13 x 75	13 x 100	17 x 120	29 x 115	26 x 95	29 x 107
Cat. No.	0578 ¹⁾	0518 ¹⁾	0519 ¹⁾	0521 ¹⁾	blood collection / urine tubes				0509	0513	0545	0546
 rotor Cat. No. 1137												
												
Cat. No.	1632	1635	1633	-	1635				1631	1641	1633	1634
boring Ø x L in mm	13 x 92	17.5 x 95	26 x 88	35 x 96	17.5 x 95				17 x 98	30 x 98	26 x 88	29 x 95
tubes per rotor	18	6			6				6	3	6	
max. RCF ¹⁾	3,944	3,783	3,703	4,025	3,783		2,978	3,783	3,824	3,824	3,703	3,904
radius in mm	98	94	92	100	94		74	94	95	95	92	97
run-up in sec	20											
run-down in sec, braked	17											

¹⁾ Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers. The max. RCF for glass tubes annotated with footnote ¹⁾ is 4,000.

ACCESSORIES


























Angle rotor, 12-place



$\angle 35^\circ$
 $n = 6,000 \text{ min}^{-1}$
 max. RCF 4,146




Cat. No. 1139

capacity in ml	0.5	5	15	1.1 – 1.4	2.6 – 3.4	2.7 – 3	4.5 – 5	4.9	7.5 – 10
Ø x L in mm	10.7 x 36	12 x 75	17 x 100	8 x 66	13 x 65	11 x 66	11 x 92	13 x 90	15/16 x 92
Cat. No.	Pediatric	0553 ¹⁾	0518 ¹⁾	blood collection / urine tubes					
 rotor Cat. No. 1139									
									
Cat. No.	1063-6 (6 pcs.)	1054-A	-	1054-A			-		
boring Ø x L in mm	11 x 35	13.5 x 60	17.7 x 88	13.5 x 60			17.7 x 88		
tubes per rotor	12	12	12	12			12		
max. RCF ¹⁾	2,777	3,300	4,146	3,300			4,146		
radius in mm	69	82	103	82			103		
run-up in sec	16								
run-down in sec, braked	16								

capacity in ml	10	1.6–5	4–7	8	8.5–10	12	15
Ø x L in mm	15x102	13x75	13x100	16x125	16x100	17 x 102	17 x 120
Cat. No.	blood collection /urine tubes						0509
 rotor Cat. No. 1139							
							
Cat. No.	-	1054-A	1058	-			
boring Ø x L in mm	17.7 x 88	13.5x60	13.5x79	17.7x88			
tubes per rotor	12	12	12	6	12	6	6
max. RCF ¹⁾	4,146	3,300	4,146				
radius in mm	103	82	103				
run-up in sec	16						
run-down in sec, braked	16						

TECHNICAL DATA



TECHNOLOGY		EBA 280		EBA 280S	
Small centrifuge, without rotor					
Power supply ¹⁾		200–240 V 1 ~	100–127 V 1 ~	200–240 V 1 ~	100–127 V 1 ~
Frequency		50–60 Hz	50–60 Hz	50–60 Hz	50–60 Hz
Consumption		185 VA	185 VA	330 VA	330 VA
Emission, Immunity		EN/IEC 61326-1, class B	FCC class B	EN/IEC 61326-1, class B	FCC class B
	Max. capacity	6x50 ml	6x50 ml	6x50 ml	6x50 ml
 /	Max. RPM (speed)	6,000 min ⁻¹	6,000 min ⁻¹	6,000 min ⁻¹	6,000 min ⁻¹
	Max. RCF	4,146	4,146	5,071	5,071
Running time		1 s–99 min :59 s, ∞ continuous run, short cycle mode (impulse key)			
Dimensions (HxWxD)		242x326x400 mm	242x326x400 mm	242x326x400 mm	242x326x400 mm
Weight		approx. 11 kg	approx. 11 kg	approx. 11 kg	approx. 11 kg
Cat. No.		1101	1101-01	1102	1102-01

¹⁾ Other voltages on request.



Hettich centrifuges comply with all relevant EU standards in effect and conform to the European level of quality and safety for medical devices. Evidence is provided by national and international test marks such as IEC 61010 or the CE conformity. The ISO 9001, ISO 13485 and ISO 14001 certificates accredited to the company bear witness to the extreme care and responsibility Hettich puts into the manufacturing of centrifuges and their accessories.



Our certification as an “Authorised Economic Operator” enables accelerated customs clearance.



www.hettichlab.com

Hettich

LAB TECHNOLOGY